

# SHOWERWALL GLOSS ACRYLIC DATA SHEET



Details of our Gloss Acrylic range.

**ACRYLIC PANELS** - Designs with a gloss finish from The Acrylic Collection

## PRODUCT OVERVIEW

**Product Name:** Showerwall Acrylic  
**Material Type:** Extruded Acrylic  
**Finish:** Gloss  
**Application:** Interior Walls

Showerwall's Acrylic Collection can create a striking accent wall, perfect for breaking up the space or used as a statement within the bathroom. The 4mm acrylic panels are rear printed to give a glass-like surface. These panels features a high-gloss finish that amplifies colour and detail in digital imagery - creating a vibrant high-shine effect.

## KEY FEATURES & BENEFITS

100% waterproof  
Smooth glass-like finish  
Hygienic and easy to clean  
Pattern matched designs  
Can be installed directly over tiles

## DIMENSION TOLERANCES

Width +/- 5.0mm  
Height +/- 5.0mm  
Thickness +/- 5.0mm

## PRODUCT OVERVIEW

Square Edge	2400mm x 896mm	10.5kg
	2400mm x 1200mm	14.29kg

## FABRICATION & INSTALLATION

- Showerwall acrylic panels must be fitted by a qualified installer
- Use the correct tools for installation, please refer to the full Showerwall Acrylic installation guide for this
- Always use the installation kit contents for adhering and sealing acrylic panels
- If using a router to cut panels, make sure a guide is used with a straight TCT cutter and a minimum cutting speed of 4500 m/min
- If using a jigsaw to cut panels, choose a large-tooth blade
- When cutting and drilling panels, always fully support panels on a sacrificial board and clamp securely
- Use HSS bi-metal twist drills (60 – 90 point angle), drill at low speed and ensure all holes are de-burred after drilling

## FIRE RATINGS / PERFORMANCE

**Heat Distortion:** D684, 100°C  
**Heat Distortion Temp:** ASTM D 648, 100°C  
**Vicat Softening Point:** D1525, 118°C  
**Reaction to Fire:** EN13501-1, Class E  
**Smoke Density:** ASTM D 2843, 10.3%  
**Thermal Conductivity:** D1525, 118°C

## STORAGE & HANDLING

- Store flat on a fully supported pallet
- Keep in a dry, temperature-controlled environment
- Avoid direct sunlight prior to installation
- Do not store panels on edge or propped up against a wall

# SHOWERWALL GLOSS ACRYLIC DATA SHEET

## CARE & MAINTENANCE

---

- Abrasive cleaners and bleaches must not be used on Showerwall panelling.
- Showerwall provide a cleaner that has been selected and tested for use with our products.

## ACRYLIC INSTALLATION KIT

---

Delivered with your Showerwall panels you will find an installation kit to aid fitting – there will be one kit supplied per panel. Each kit contains the following:



2 x Alcohol Surface Preparation Wipes

Removes dust and grease to promote optimal adhesion prior to installation.



3 x Translucent Silicone Sealant

High-grab, moisture-resistant silicone for full-surface bonding and sealing of joints, corners and perimeter edges. Creates a durable, watertight finish.



12 x Double-Sided Adhesive Pads

Provides temporary positioning support and immediate panel hold while silicone cures. Helps ensure accurate alignment and reduced slip.

## WARRANTY

---

When installed correctly using the recommended fitting guide, Showerwall is guaranteed to be free from defects for 30 years, from the date of purchase. A copy of the Showerwall guarantee is available to download from [www.showerwall.co.uk](http://www.showerwall.co.uk).

Note your Showerwall panels carry a 30-year guarantee that is limited to domestic use against manufacturing defects, only when registered online at [www.showerwall.co.uk](http://www.showerwall.co.uk). If the purchase of your panels is not registered within 28 days of the installation being completed, then the guarantee is reduced to a 15-year term.