Fluid monobloc

Product Finish: Chrome	Product code: AT1169 EAN13 barcode: 5060048381863



Note: the image shown may not reflect the product finish, chrome finish is typically depicted.


Product features:

- Subtle soft sweeping design form
- Quarter turn handle action for precise flow control
- Metal construction throughout
- Antisplash spout supplied as standard
- Supplied compete with flexible tail pipes for fast simple fitting

Additional information / Parts included:

Includes 2.5 & 2mm Allen key & triangular stabiliser

Product dimensions:



- **Overall Height / projection:** 360 mm
- **Exit reach:** 220 mm
- **Exit height:** 220 mm
- **Centre distance(s):**


- **Base diameter(s):** 59 mm
- **Recommended hole diameter:** Ø 35 mm
- **Max. surface depth:** 70 mm

- **Spout diameter:** n/a mm
- **Spout aerator size:** 22m

Packaged properties:

Box length: 575mm	**Box depth:** 75mm
Box width: 355mm	**Units per outer:** 5
Tap only weight: 2.48kg	**Boxed weight:** 3.40kg

Product flow characteristics:



- **Min / Max water pressure:** 0.40 / 5.5 bar
- **Recommended / Max water temperature:** 46°C / 70°C
- **Part G - Mixed flow rate at 3 bar (litres / min):** 13.92

- **Control valve type:** Ceramic disc QT
- **Product flow characteristics:** Single flow
- **Non return valve(s):** Hot & cold (integral to tails)

- **Aerator type:** Plastic mesh diffuser
- **Accepts revolve / spray areator:** No
- **Spout connection method:** Grub screw

- **Tail pipe inlet / outlet size:** M12 / 1/2" BSP Male
- **Inlet pipe type / length:** flexible stainless braided hose / 245 mm

Care instructions summary:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of sink & worktop cleaners can also cause damage, so rinse with clean water after using, avoid contact with any abrasives

Warranty Summary (Full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year
- O-rings, hoses & gaskets warranted for 1 year