

Deck Mounted Bath Shower Mixer with Shower Handset



Product features:

- Metal & ABS construction
- Quarter turn handle action for precise flow control
- Custom designed for lower range pressures
- Swivel spout for maximum flexibility
- Single spray pattern showerhead


Packaged properties:

Box length (mm): 380 Box depth(mm): 105 Box width(mm): 255 Boxed weight (Kg): 3.9 Includes pop up waste?: No

Additional comments:

Includes fixed shower bracket & round showerhead

Product dimensions:




 Product mounted where: Surface • Recommended hole size: 32 mm

 Overall Height / projection: 300 mm 107 mm • Exit reach: • Exit height: 223 mm • Base size: 50 mm

- Inlet centre distance(s): 180 mm
- · Min. fitting depth required:
- · Max. surface depth:

Product flow characteristics:



- Min / Max water pressure (bar): 0.20* / 5.00 *Detailed minimum pressure requirements for this product: Bath 0.2, Shower 0.3 (bar)
- Part G max. mixed flow rate at 3 bar (I/m): bath=45.6, shower=21.5
- Inlet connection type / length: Fixed / 65 mm
- Inlet (plumbing connection) / outlet size: 3/4" M /
- Product flow characteristics: Single flow Non return valve(s) supplied or position:
- Aerator type: White flow straightener
- Control valve type: 1/2" QT CD (8-20) • Includes output diverter?: Yes
- Inlet meshed particle filters included: • Shower hose type / length: Smoothflex / 1.50 m
- Warranty Summary (full details available on request):
- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year O-rings, hoses & gaskets warranted for 1 year

Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives