



### Product features:


- Metal construction throughout
- Single lever control for effortless single handed control
- · Supplied compete with flexible tail pipes for fast simple fitting
- · Leading design features requiring high pressure
- · Modern minimalism with flair

Packaged properties:

Box length (mm): 490 Box depth(mm): 700
Box width(mm): 290 Boxed weight (Kg): 3.0

Includes pop up waste?: No Additional comments:

## **Product dimensions:**




Product mounted where: Surface
 Recommended hole size: 35 mm

• Overall Height / projection: 358 mm • Exit reach: 192 mm • Exit height: 235 mm • Base size: 50 mm

• Inlet centre distance(s): N/A mm

• Min. fitting depth required: N/A mm • Max. surface depth: 60 mm

# Product flow characteristics:



- Min / Max water pressure (bar): 1.00\* / 5.50
- Part G max. mixed flow rate at 3 bar (I/m): 10.71
- Inlet connection type / length: Flexi / 600 mm
- $\bullet$  Inlet (plumbing connection) / outlet size: 1/2" F / M8
- Product flow characteristics: Single flow Non return valve(s) supplied or position: no
- Aerator type: Rectangular Neoperl antisplash (high flow)
- Control valve type: Single lever (25mm)
- Includes output diverter?: N/A
- Inlet meshed particle filters included: N/A
- Shower hose type / length: N/A / N/A

#### Warranty Summary (full details available on request):

- Materials and workmanship defects warranted for 5 years
- Valves and working parts warranted for 5 years
- Surface warranty defects warranted for 1 year O-rings, hoses & gaskets warranted for 1 year

## Care instructions:

- Clean the mixers and showers regularly as required, using soap, do not use any other cleaners.
- Regular cleaning will prevent the build up of lime scale and dirt
- After cleaning rinse thoroughly with clean water to remove any cleaner residue
- Residues of liquid soaps, shampoos and shower foams can also cause damage, so rinse with clean water after using, avoid contact with any abrasives